



## Everest

The Everest has a sleek two toned aesthetic that will enhance any space. The sturdy and ergonomic faucet handles are 7" higher than traditional units, which enables effortless dispensing. The removable side panels facilitate access to all electrical components for easy maintenance and servicing. The innovative removable reservoir and faucet assembly make the cleaning and sanitizing process quick and simple.

### Everest: Hot & Cold



**Reservoir / faucet assembly - patent pending**



**DryGuard™ - patented no spill system**



**Integrated cup dispenser**

### Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase 100-115VAC 60Hz
Standard current		Hot & Cold: 4.3~4.8A
Power Consumption	Cold	75W
	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Temp control	thermostat (ON 12°C±1.5°C, OFF 2°C±1.5°C)
	Capacity	2.4L (0.6 gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Safety device	Bimetal (Manual reset: 95°C OFF)
	Temp control	Bimetal (83°C)(181.4°F)
	Capacity (External Heater)	1.1L (0.3 gal)
Refrigerant charge		30g (1.1 oz)
Noise(sound power level)		43dB(A)
Product weight		Hot & Cold: 12.2kg (27.0 lb)
Product boxed weight		Hot & Cold: 13.5kg (29.8 lb)
Product dimensions		358.5(W) X 342(D) X 1053(H)mm 14.1"(W) X 13.5 "(D) X41.4"(H)
Product boxed dimensions		330(W) X 330(D) X 1070(H)mm 13.0"(W) X 13.0 "(D) X 42.1"(H)
Loading quantity		20' Container: 238Units 40' Container: 504Units
IEC protection class		Class 1