

Water Coolers

Standard Series

Consistency in performance, competitive pricing & one piece blow-molded cabinet of high-density polyethylene with UV resistance additives make this cooler a popular long-life rental unit.

Model:

Standard H/C (Hot and Cold)

Standard C/C (Cook and Cold)

Standard NS H/C (Hot and Cold)

Standard NS C/C (Cook and Cold)

- Graceful design, easy to maintain and convenient to use
- Food grade stainless steel (SUS304) hot tank and cooling tank
- Large and durable drip tray
- High quality and efficient compressor for reliable and consistent performance
- Available in White color
- 2 years limited warranty



Standard Series are
Energy Star rated

Standard Series

Technical Data & Specifications

Cabinet & Chassis: One piece blow molded high-density polyethylene plastic. Resists cracking, fading and yellowing. Color molded in to hide scrapes caused by rough usage. Easily removed for access to interior components. The shock absorbing base is made of ABS plastic that will never rust.

Cold Water Refrigeration Unit: Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with "OFF" position that is easily accessible on the rear of the unit.

Cold Water Reservoir: Food grade stainless steel type SUS304, 1 gallon (3.8 liter) reservoir. Provides superior chilling for great tasting water. Highly polished surface is easy to clean and maintain.

Hot Water Tank: Food grade stainless steel type SUS304, 0.32 gallon (1.2 liter) capacity. The 520 watts heating element ensures precise temperature control. Removable thermostat and heating element ease service.

Electrical:
Cooler operates on 115 volts, 60 Hertz
Refrigerant:
All units contain HFC-134a refrigerant.

Shipping Dimension

Height	39.0 in. (990mm)
Width	12.8 in. (325mm)
Depth	13.2 in. (335mm)

Shipping Weights

Cook & Cold	33.1 lbs. (15kg)
Hot & Cold	35.3 lbs. (16kg)

Cooler Dimension

Height	37.0 in. (940mm)
Width	12.2 in. (310mm)
Depth	12.6 in. (320mm)

Cooler Weights

Cook & Cold	30.9 lbs. (14kg)
Hot & Cold	33.1 lbs. (15kg)



Standard Series are Energy Star rated



Cooling and Heating Capacities Room Temperature	°F (°C)	70° (21°)	80° (27°)	90° (32°)
Quality for cold water Served per hour	GPH LPH	1.2 4.5	0.9 3.2	0.5 1.9
Number of 3oz. (89ml.) Cups of 50°F (10°C) water Served per hour		53	38	22
Hot water deliver at 180°F (82°C) [for Hot & Cold model only]		45 cups of 6oz. (178ml.) per hour		



The rounded cabinet and fluted front give the Top Load a classic Greek column design. While being esthetically pleasing, the polyethylene cabinet's smooth finish is easier to clean and refurbish. Featuring the patented **DryGuard™** no spill system, you're protected from faulty or damaged water bottles. Other features included are: three color choices, Energy Star rated and noise dampening technology.

Hot & Cold



Touch Guard®
hot water faucet



Removable drip tray



Hot water ON
and **OFF** switch

Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase
		100-115VAC 60Hz
Standard current		Hot & Cold: 6.2A
Power Consumption	Cold	70W
	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Capacity	2.6L (0.7 us gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Temp control	82-89°C (179.6-192.2°F)
	Capacity (External Heater)	2L (0.5 us gal)
	Capacity (Internal Heater)	1L (0.3 us gal)
Refrigerant charge		27g (0.95 oz)
Product weight		Hot & Cold: 13.7kg (30.1 lb)
Product boxed weight		Hot & Cold: 14.8kg (32.6 lb)
Product dimensions		312(W) X 314 (D) X 980(H)mm
		12.2"(W) X 12.4"(D) X 38.6"(H)
Product boxed dimensions		320(W) X 330(D) X 1000(H)mm
		12.5"(W) X 13.0"(D) X 39.4"(H)
Loading quantity		20' Container: 252 Units
		40' Container: 518 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB, CCC, SASO,EPA





A robust bottle water dispenser with a classic design. The Top Load is the perfect water cooler for the traditional home and office delivery. Featuring Stainless tanks and one-piece blow molded cabinet, the Top Load is built to perform and backed by the company known for innovation, quality and support.

Hot & Cold



Tomlinson™ Touch
Guard®
hot water faucet



Removable drip tray



Carry handle

ITEM		SPECIFICATIONS
Power rating		Single phase
		100-115VAC 60Hz
Standard current		HOT & COLD: 4.5-5.1A
Power Consumption	Cold	85W
	Hot	400W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	5-10°C (41-50°F)
	Capacity	3.47L (0.9 gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Temp control	82-89°C (179.6-192.2°F)
	Capacity (External Heater)	1.47L (0.3 gal)
Noise(sound power level)		44dB(A)
Refrigerant charge		34g (1.2 oz)
Product weight		HOT & COLD: 12kg (26.5 lb)
Product boxed weight		HOT & COLD: 13kg (28.6 lb)
Product dimensions		320(W) X320(D) X980(H)mm
		12.6"(W) X 12.6"(D) X 38.6"(H)
Product boxed dimensions		325(W) X 325(D) X 1000(H)mm
		12.8"(W) X 12.8 "(D) X 39.4"(H)
Loading quantity		20' Container: 238Units
		40' Container: 504Units
IEC protection class		Class 1
Certifications		C-CSA-US, EPA