



## Storm (Bottom-Load water dispenser)

The Bottom-Load means no more lifting heavy bottles, just open the front door and the bottle slides into the base of the cooler with little effort. The Storm features an easy to remove reservoir system, that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Model: Storm: **Hot & Cold**




LED Night Light, Low bottle Indicator and replace SmartFlo™ SF-1 Indicator



Hidden Bottle with Space - saving Sliding front Door



Replaceable Reservoir System - SmartFlo™ SF-1 Water Cartridge



### Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase
		100-115VAC 60Hz
Standard current		Hot & Cold: 4.8~5.3A
Power Consumption	Cold	70W
	Hot	450W
I <sub>d</sub>	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Temp control	thermostat (ON 8 °C ±1.5°C, OFF 4 °C ±1.5°C)
	Capacity	1.6L (0.42 gal)
Hot	Heater	Internal heater
	Temp range	76-92°C (168.8-197.6°F)
	Safety device	Bimetal (Manual reset: 95°C OFF)
	Temp control	Bimetal (85°C)(185°F)
	Capacity (Internal Heater)	1.1L (0.3 gal)

Refrigerant charge	35g (1.2 oz)
Noise(sound power level)	Pump:55dB(A); Compressor:43dB(A)
Product weight	Hot & Cold: 14.5kg (32.0 lb)
Product boxed weight	Hot & Cold: 16.2kg (35.7 lb)
Product dimensions	320(W) x 340(D) x 1116(H)mm
	12.6"(W) X 13.4"(D) X 44.0"(H)
Product boxed dimensions	340(W) X 380(D) X 1165(H)mm
	13.4" (W) X 15.0" (D) X 45.9" (H)
Loading quantity	20' Container: 204 Units
	40' Container: 420 Units
IEC protection class	Class 1
Certifications	C-UL-US, CE, CB, EPA